

# Safe, multi-layer KORUSER floor protection



Easy Application



Water-Proof



Save Time



Anti-Slip



Breathable



Absorbent



Reusable

- ✓ Turn off floor heating before laying Koruser
- ✓ Wipe or vacuum clean the underlying surface for better adhesion.
- ✓ Ambient temperature 50-77 F
- ✓ Ambient humidity less than 60%
- ✓ Wait at least 72 hours after applying any type of finish coat on the underlying flooring.  
Follow the drying time instructions indicated by the finish coating manufacturer and always perform a small test to ensure the floor is fully dry.
- ✓ Apply the product in 4" overlapping strips.

Size : 36" x 100' ( 300 sqft )



## Hassan Tekstil Sanayi ve Ticaret A.Ş.

Akçaburgaz Mah., Hadımköy Yolu, No:88, Esenyurt, 34522, İstanbul, Turkey

Tel : +90 212 886 53 30

Faks : +90 212 886 53 33

e-mail : info@koruser.com.tr

web : www.koruser.com.tr

# Safe, multi-layer FLOOR PROTECTION

# KORUSER



## Hassan Tekstil Sanayi ve Ticaret A.Ş.

Akçaburgaz Mah., Hadımköy Yolu, No:88, Esenyurt, 34522, İstanbul, Turkey

Tel : +90 212 886 53 30

Faks : +90 212 886 53 33

e-mail : info@koruser.com.tr

web : www.koruser.com.tr